

SHARP®



Check out this compact LCD projector - the **NotevisionC40**. From color-coded user interface points and easily identifiable icon-based adjustment buttons, to full automatic synchronization of images and input sources. This projector is bound to make your life a little easier.

The NotevisionC40 will accept input signals ranging from VGA and SVGA to it's native XGA resolution and up to 1600 x 1200 (UXGA). It projects each input mode in exacting detail without the need for any manual adjustments.

It's compatible, versatile, and very easy to use. Just plug it in to your data or video source and let the presentation begin. Your audience will love it.

The NotevisionC40 may be compact, but with 2000 ANSI lumens this small package will create major impact.

Truly presentation technology at its best!

ADVANCED FEATURES

- * 2000 ANSI Lumens Brightness with 90% Uniformity (CCR)
- * S.A.P.S. for Remote Projector Control and Self Diagnostics
- * Two Separate Data Inputs for PC or Mac plus Monitor Out
- * Two Separate Video Inputs (Composite and S-Video)
- * "autoSYNC" for Automatic Image Perfection
- * Intelligent ImageACE Resizing
- * 1.3:1 x Manual Zoom/Focus Lens
- * International Power Supply (100-240V AC)
- * Wireless "Power Remote" with Mouse Control and Laser Pointer
- * Built-in 3 watt Audio System
- * Digital Keystone Correction with Edge Smoothing
- * 3D Digital Uniformity
- * Designed to Fit in an Airplane Overhead Complete w/ Notebook PC
- * "PresenterPAK", The Sharp Exclusive Feature-set - Making it Simple to "Connect, Perfect, Project"
- * DTV Compatible 480i/480p/720p/1080i

PROJECTION DISTANCES

Screen Diagonal	Screen Width	Screen Height	Minimum Distance	Maximum Distance
40"	32"	24"	4'8"	6'1"
60"	48"	36"	7'1"	9'3"
84"	67"	50"	9'11"	13'1"
100"	80"	60"	11'11"	15'6"
150"	120"	90"	17'8"	23'1"
200"	160"	120"	23'6"	30'7"
300"	240"	180"	35'4"	46'

Approx. Min / Max Projection Distance from Screen to Front of Lens

*Design and specifications are subject to change without notice. All trademarks are property of their respective holders.

SPECIFICATIONS

Resolution	XGA (1024 x 768)
TV Lines	750 TV Lines
Panel Type	3 - 0.9" Polysilicon TFT LCD
H & V Frequency	fH 15-126 kHz / fV 43 - 200 Hz
Dot Clock	230 MHz
PC Compatibility	UXGA (1600 x 1200) w/ ImageACE Resizing
Mac Compatibility	21" up to 1280x1024 w/ ImageACE Resizing
WS Compatibility	1280 x 1024 (various modes w/ ImageACE Resizing)
Video System	NTSC/DTV/PAL/SECAM - Interlaced or Progressive Scan DTV/HD Compatible 480i/480p/720p/1080i
Resizing	Advanced ImageACE Resizing - up to UXGA
Brightness	2000 ANSI Lumens w/ 90% CCR
Contrast Ratio	400:1
Lens Type	1.3:1 Manual Zoom and Focus
PC Control	RS-232C
Remote Control	IR w/ Mouse Control, Laser Pointer
IR Carrier Frequency	38 kHz
Audio System	3 Watt Monaural
Lamp	200 NSH, User Replaceable
Lamp Part No.	BQC-XGC40XU/1
Fan Noise	39 dB
Power Source	100-240V AC, 50/60Hz
Power Consumption	300 Watt
Heat Dissipation	1,130 BTU/hour
Dimensions	9.0" x 4.8" x 12.2" (main body)
Weight	10.6 lbs.
Limited Warranty	3 Yrs. Parts/Labor & 3 Yrs. Sharp Express Repair, Lamp 90 Days
Presentation Tools	"PresenterPAK"

INPUTS/OUTPUTS

- 2 - RGB/Computer Inputs [15 pin HD Female]
- 1 - Computer/RGB Output [15 pin HD Female]
- 2 - Separate Video Inputs [Composite (RCA) and S-Video (4 pin DIN)]
- 2 - Stereo Audio Inputs (RCA pair L/R; 3.5mm Stereo Minijack)
- 1 - Audio Out (3.5mm Stereo Minijack)
- 1 - RS-232C Serial Port (9 pin D-sub Male)

INCLUDED ACCESSORIES

Backlit Wireless Remote with Laser Pointer and Mouse Control, Two AA batteries, 9' RGB Signal Cable, 12' Grounded AC Cord, 270° Wireless Mouse IR Receiver, USB Mouse Adapters, 9' Audio cable, DIN DSub RS-232C adapter, Air Filter, Lens Cap, Owners Manual, Sharp Advanced Presentation Pro Software (S.A.P.S.)

OPTIONAL ACCESSORIES

- AN-C100PCBAG** Soft Sided Carry-on Bag (projector & PC)
- AN-C100BAG** Soft Sided Carry-on Bag (projector only)
- AN-C100CC** Hard Shell Carrying Case (projector only)
- AN-C100WB** Hard Sided Bag w/wheels (projector & PC)
- AN-C100SC** "ATA" Style Shipping Case for Projector
- AN-XGCM53** Ceiling Mounting Bracket
- AN-EP101B** Extension Tube for Ceiling Mount
- AN-JT200** Angle Mount Joint for Ceiling Mount

SHARP ELECTRONICS CORPORATION
 LCD Products Group, Sharp Plaza, Mahwah, NJ 07430-2135
 E-mail: ProLCD@SharpSEC.com
1-888-GO-SHARP

www.SharpLCD.com/Notevision

